

## Restraint Cage

## Catalog # 44114

11ga. 304 Stainless Steel construction.

18ga. SS Sheet.

Approx. overall size of Unit is 34" wide x 72" lg. x 52"

tall (with casters). (NTE 72"Long)

Inside operating dimensions are 30" wide x 70" long x

45" tall. (can be adjusted)

Caster Base and Main Frame components constructed

of SS 1" X 1" Box Tube.

Unit is supported on SS 5" Casters that will be

outboard the main frame of Cage.

One fixed side wall of the unit has Removable 3/8"

diameter rods on 3" centers.

Unit has open top with same 3/8" dia. Cross Rods on

3" centers.

The Restraint Wall has 3/8" diameter rods on 3" cen-

ters.

Restraint Wall operates using a removable crank

handle turning a SS Acme Screw shaft.

Removable Crank Handle provided.

Restraint Wall is guided and glides on bearing system

for easy operation.

Guillotine Style Doors at either end have removable

3/8" diameter rods on 3" - 6" centers.

Spring loaded stainless steel latched provided on

guillotine doors.

Removable SS 16ga. Waste Pan provided with latch.

Solid Stainless Diamond Tread Flooring provided for

easy cleaning.

Removable Wall side wall has 3/8" diameter rods on 3"

centers.

Unit can be equipped with a ramp.

Size of Unit and Design can be customized to better

suit your needs.





